Dimensions



Model (kW)	A	B	C	D	E
kW≤3.6	750	295	265	581	736
3.6 < kW≤5.6	950	295	265	781	936
5.6 < kW≤8.0	1200	295	265	1025	1186

Specification

Model			MIH15GHN18	MIH22GHN18	MIH28GHN18	MIH36GHN18
Power supply			1-phase, 220-240V, 50/60Hz			
Cooling[1]	Capacity	kW	1.5	2.2	2.8	3.6
		kBtu/h	5.1	7.5	9.6	12.3
	Power input	W	18	21	24	27
Heating[2]	Capacity	kW	1.7	2.4	3.2	4
		kBtu/h	5.8	8.2	10.9	13.6
	Power input	W	18	21	24	27
Air flow rate[3]		m^3/h	460/440/420/400/380/360/340	500/470/440/410/390/370/340	540/510/470/430/400/370/340	580/540/500/460/420/380/340
Sound pressure level[4]		dB(A)	32/31/30/30/29/28/27	33/32/31/30/29/28/27	35/34/33/32/31/30/28	37/36/34/33/31/30/28
Sound power level		dB(A)	45/44/43/43/42/41/40	46/45/44/43/42/41/40	50/49/48/47/46/44/42	54/53/51/50/48/46/44
Unit	Net dimensions (W×H×D)	mm	750×295×265	750×295×265	750×295×265	750×295×265
	Packed dimensions (W×H×D)	mm	875×385×360	875×385×360	875×385×360	875×385×360
	Net/Gross weight	kg	9/11.5	9/11.5	10/12.5	10/12.5
Refrigerant type			R410A/R32			
Pipe connections	Liquid/Gas pipe	mm	Ø6.35/Ø12.7	Ø6.35/Ø12.7	Ø6.35/Ø12.7	Ø6.35/Ø12.7
	Drain pipe	mm	OD Ø16	OD Ø16	OD Ø16	OD Ø16

Model			MIH45GHN18	MIH56GHN18	MIH71GHN18	MIH80GHN18
Power supply			1-phase, 220-240V, 50/60Hz			
Cooling[1]	Capacity	kW	4.5	5.6	7.1	8
		kBtu/h	15.4	19.1	24.2	27.3
	Power input	W	30	40	50	65
Heating[2]	Capacity	kW	5	6.3	8	9
		kBtu/h	17.1	21.5	27.3	30.7
	Power input	W	30	40	50	65
Air flow rate[3]		m^3/h	720/670/620/560/510/460/410	860/780/700/620/550/480/410	1220/1120/1030/940/850/750/660	1380/1260/1140/1020/900/780/660
Sound pressure level[4]		dB(A)	37/35/33/32/31/30/29	41/39/37/35/33/31/29	44/42/40/38/36/34/32	45/43/41/39/37/35/32
Sound power level		dB(A)	54/52/50/49/48/46/44	56/54/52/50/48/46/44	58/56/54/52/50/48/46	60/57/55/53/50/48/46
Unit	Net dimensions (W×H×D)	mm	950×295×265	950×295×265	1200×295×265	1200×295×265
	Packed dimensions (W×H×D)	mm	1075×385×360	1075×385×360	1315×385×360	1315×385×360
	Net/Gross weight	kg	11.5/14	11.5/14	15/18	15/18
Refrigerant type			R410A/R32			
Pipe connections	Liquid/Gas pipe	mm	Ø6.35/Ø12.7	Ø6.35/Ø12.7	Φ9.52/Φ15.9	Φ9.52/Φ15.9
	Drain pipe	mm	OD Ø16	OD Ø16	OD Ø16	OD Ø16

Notes:
1. Indoor temperature 27°C DB, 19°C WB; outdoor temperature 35°C DB; equivalent refrigerant piping length 7.5m with zero level difference.
2. Indoor temperature 20°C DB; outdoor temperature 7°C DB, 6°C WB; equivalent refrigerant piping length 7.5m with zero level difference.
3. Air flow rate are from the highest speed to the lowest speed, total 7 rates for each model.
4. Sound pressure level is from highest level to lowest level, total 7 levels for each model. Sound pressure level is measured 0.8m below the unit in an anechoic chamber.
5. The dimension is only the body size, excluding the size of the installation lug, connecting copper pipe, etc. For detailed dimensions, please refer to the installation manual.

B-V8GH202307

Midea

V8 INDOOR UNIT
Wall Mounted

DISCOVER
RELIABLE COMFORT

Why Choose V8 Wall Mounted

LOFT have limited floor height and the installation of Wall Mounted units requires a certain height from the ceiling, which both reduces space for movement and is unsightly.

Ceiling Mounting

The Wall Mounted new heat exchanger is designed to meet the installation requirements close to the ceiling, and the minimum distance from the ceiling is ***3cm***.

There is some distance from ceiling

The distance from the ceiling is 3cm

When resting, the air conditioner in the bedroom is always noisy and makes a squeaking noise that affects the quality of sleep.

Quiet Operation

For Wall Mounted throttling parts and drain pumps adopt closed design, reducing noise. The minimum noise level of Wall Mounted is as low as ***27dB(A)***.



My child is allergic and often sneeze. I always thought that he catches a cold, finally found that he is dust allergy.

Self-cleaning function*

The heat exchanger is cleaned of dirt by freezing frost and then autoclaved, improving the quality of the air delivered and creating a healthy environment.

* Heat exchanger self-cleaning function can be available only when V8 Mini is connected.

Human Detect Sensor*

Using millimeter-wave radar sensor controller automatically turns indoor units on or off upon detecting that the room is occupied or unoccupied, ensuring climate control whilst minimizing energy consumption.

The indoor unit automatically runs when detecting human body

The indoor unit automatically stops when detecting absence

*This function is available as a customization option for V8 Wall Mounted.

Free Drainage without Space Restrictions

The Wall Mounted can realize horizontal drainage, downward drainage, upward drainage, making installation more flexible.



Most conventional Wall Mounted unit does not have a drain pump and the condensate pipe can only be installed underneath the unit, relying on gravity to drain the condensate to the nearest window.

When the condensate pipe is blocked, condensate can drip down onto the floor and damage it.

Bi-directional Coanda Airflow

With bi-directional Coanda airflow delivery technology, the cold air does not blow directly on people and the hot air warms up evenly from the feet for better comfort.